

ELECTRO-MATIC 623 Plug angled rotatable INTEGRATED, INC.

9-pin
insulation insert uncoded
housing code 1
EMV - shielding

Technical Data

number of pins 9
temperature range -20 °C to 130 °C
clamping range Ø 7.5 mm to Ø 12.0 mm
protection type when connected IP 66/67
rotation range 330°

Electrical Data

rated current
rated voltage
rated insulation voltage (L-L)

signal

max. 10 A*
160 V (AC/DC)
2500 V

mating cycles 500

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree 3
over voltage category III
max. height for operation 2000 m

Material

housing zinc diecast / nickel plated
insulation insert PBT, UL 94 / V0
seals FKM
contacts brass / gold plated
contacts brass / gold plated
clamp ring brass / nickel plated

Contacts

Item: 60.001.11
type Contact Socket 1.0 mm
cross section crimp/ 0.14 - 1.00 mm²
contact resistance < 5 mOhm

Item: 60.012.11
type Contact Socket 2.0 mm
cross section crimp/ 0.35 - 2.50 mm²
contact resistance < 3 mOhm

Tools (not part of product contents)

digital crimping tool for 0,6mm/1,0mm/1,5mm/2,0mm-contacts
Item: C0.235.00

analog crimping tool for 1 mm-/2 mm- contacts
Item: C0.201.00

analog crimping tool for 1 mm contacts
Item: C0.101.00

A SD A 071 FR 29 55 0150 A00




Contact Arrangement
mating view



Contact Socket 1.0 mm
crimp/ 0.14 - 1.00 mm²
Item: 60.001.11



Contact Socket 2.0 mm
crimp/ 0.35 - 2.50 mm²
Item: 60.012.11



Main Dimensions
Plug angled rotatable

*for max. wire cross-section
pay attention to the
cross-section of used contacts

Copyright by Electro-Matic Integrated, INC.
All rights, including rights created by patent grant or registration
of a utility model or design, are reserved.
Noncompliance will result in seeking damages.

This document is for information only and before utilization
the user must reconfirm actuality.
Subject to technical changes.

Electro-Matic Integrated, INC.
23410 Industrial Park Court
48335 Farmington Hills, MI
USA

E-Mail: ConnectivityEng@electro-matic.com
Web: www.emintegrated.com

issue: 04.07.2020