

Technical Data

number of pins	12
temperature range	-20 °C to 130 °C
clamping range	Ø 6.0 mm to Ø 10.0 mm
protection type	when connected IP 66/67

Electrical Data

rated current	max. 7 A*
rated voltage	160 V (AC/DC)
rated insulation voltage (L-L)	2500 V

mating cycles	500
---------------	-----

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PBT, UL 94 / V0
seals	FKM
contacts	brass / gold plated
clamp ring	brass / nickel plated

Contacts

Item:	61.083.11
type	Contact Pin ø1.0 mm
cross section	crimp/ 0.03 - 0.34 mm ²
contact resistance	< 5 mOhm

Tools (not part of product contents)

digital crimping tool for 0,6mm/1,0mm/1,5mm/2,0mm-contacts
Item: C0.235.00

analog crimping tool for 1 mm contacts
Item: C0.101.00

A KU A 012 MR 83 41 0100 A00



Contact Arrangement
mating view




Contact Pin ø1.0 mm
crimp/ 0.03 - 0.34 mm²
Item: 61.083.11



Copyright by Electro-Matic Integrated, INC.
All rights, including rights created by patent grant or registration
of a utility model or design, are reserved.
Noncompliance will result in seeking damages.

This document is for information only and before utilization
the user must reconfirm actuality.
Subject to technical changes.

Electro-Matic Integrated, INC.
23410 Industrial Park Court
48335 Farmington Hills, MI
USA
E-Mail: ConnectivityEng@electro-matic.com
Web: www.emintegrated.com



Main Dimensions
Extension

*for max. wire cross-section
pay attention to the
cross-section of used contacts