

speedtec - ready
 17-pin
 insulation insert Code 0°
 housing code 1
 EMV - shielding

Technical Data

number of pins	17
temperature range	-20 °C to 130 °C
clamping range	Ø 6.0 mm to Ø 10.0 mm
protection type	when connected IP 66/67

Electrical Data

rated current	max. 7 A*
rated voltage	125 V (AC/DC)
rated insulation voltage (L-L)	2000 V

signal

max. 7 A*
125 V (AC/DC)
2000 V

mating cycles 500

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PBT, UL 94 / V0
seals	FKM
clamp ring	brass / nickel plated

Contacts (not part of product contents)

Tools (not part of product contents)

A KU A 014 NN 00 62 0200 A00



Contact Arrangement
 mating view




Copyright by Electro-Matic Integrated, INC.
 All rights, including rights created by patent grant or registration
 of a utility model or design, are reserved.
 Noncompliance will result in seeking damages.

This document is for information only and before utilization
 the user must reconfirm actuality.
 Subject to technical changes.

Electro-Matic Integrated, INC.
 23410 Industrial Park Court
 48335 Farmington Hills, MI
 USA
 E-Mail: ConnectivityEng@electro-matic.com
 Web: www.emintegrated.com

issue: 03.07.2020



Main Dimensions
 Extension

*for max. wire cross-section
 pay attention to the
 cross-section of used contacts