

Technical Data

number of pins 9
 temperature range -20 °C to 130 °C
 clamping range Ø 6.0 mm to Ø 10.0 mm
 protection type when connected IP 66/67

Electrical Data

rated current max. 10 A*
 rated voltage 160 V (AC/DC)
 rated insulation voltage (L-L) 2500 V

signal

max. 10 A*
 160 V (AC/DC)
 2500 V

mating cycles 500

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree 3
 over voltage category III
 max. height for operation 2000 m

Material

housing zinc diecast / nickel plated
 insulation insert PBT, UL 94 / V0
 seals FKM
 contacts brass / gold plated
 clamp ring brass / nickel plated

Contacts

Item: 60.001.11
 type Contact Socket 1.0 mm
 cross section crimp/ 0.14 - 1.00 mm²
 contact resistance < 5 mOhm

Tools (not part of product contents)

digital crimping tool for 0,6mm/1,0mm/1,5mm/2,0mm-contacts
 Item: C0.235.00

analog crimping tool for 1 mm-/2 mm- contacts
 Item: C0.201.00

analog crimping tool for 1 mm contacts
 Item: C0.101.00

A ST A 055 FR 01 41 0100 A00



Contact Arrangement
 mating view



Contact Socket 1.0 mm
 crimp/ 0.14 - 1.00 mm²
 Item: 60.001.11




Copyright by Electro-Matic Integrated, INC.
 All rights, including rights created by patent grant or registration
 of a utility model or design, are reserved.
 Noncompliance will result in seeking damages.

This document is for information only and before utilization
 the user must reconfirm actuality.
 Subject to technical changes,

Electro-Matic Integrated, INC.
 23410 Industrial Park Court
 48335 Farmington Hills, MI
 USA
 E-Mail: ConnectivityEng@electro-matic.com
 Web: www.emintegrated.com

issue: 02.07.2020



Main Dimensions
 Plug

*for max. wire cross-section
 pay attention to the
 cross-section of used contacts