

# 623 Plug for bus application

19-pin  
insulation insert Code 0°  
housing code 1  
EMV - shielding

## Technical Data

number of pins 19  
temperature range -20 °C to 130 °C  
clamping range Ø 9.0 mm to Ø 14.3 mm  
protection type when connected IP 66/67

## Electrical Data

rated current max. 7 A\*  
rated voltage 63 V (AC/DC)  
rated insulation voltage (L-L) 2000 V

mating cycles 500

## Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree 3  
over voltage category III  
max. height for operation 2000 m

## Material

housing zinc diecast / nickel plated  
insulation insert PBT, UL 94 / V0  
seals FKM  
clamp ring brass / nickel plated

**Contacts** (not part of product contents)

**Tools** (not part of product contents)

**A ST A 558 NN 00 73 0266 A00**



**Contact Arrangement**  
mating view




Copyright by Electro-Matic Integrated, INC.  
All rights, including rights created by patent grant or registration  
of a utility model or design, are reserved.  
Noncompliance will result in seeking damages.

This document is for information only and before utilization  
the user must reconfirm actuality.  
Subject to technical changes.

Electro-Matic Integrated, INC.  
23410 Industrial Park Court  
48335 Farmington Hills, MI  
USA

E-Mail: ConnectivityEng@electro-matic.com  
Web: www.emintegrated.com



**Main Dimensions**  
Plug  
for bus application

\*for max. wire cross-section  
pay attention to the  
cross-section of used contacts