

923 Plug angled 90° adjustable

6-pin
EMC - Shielding
Earth-to-Housing Connection according to VDE 0627

Technical Data

number of pins	6
power	6 (3+PE+2)
temperature range	-20 °C to 130 °C
clamping range	Ø 9.5 mm to Ø 14.5 mm
protection type	when connected IP 66/67

Electrical Data

rated current	power
rated voltage	max. 30 A*
rated insulation voltage (L-L)	630V (AC/DC)
	6000 V

mating cycles	500
---------------	-----

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PA 6.6 mod., UL 94/V0
seals	FKM
contacts	brass / gold plated
clamp ring	brass / nickel plated

Contacts

Item:	60.252.11
type	Contact Socket 2.0 mm
cross section	crimp/ 0.35 - 2.50 mm ²
contact resistance	< 3 mOhm

Tools (not part of product contents)

digital crimping tool for 1mm-/2 mm- contacts
Item: C0.236.00

analog crimping tool for 1 mm-/2 mm- contacts
Item: C0.201.00

positioning insert for ø2mm contacts
Item: C0.004.00

B SD A 107 FR 03 42 0200 A00




Contact Arrangement
mating view



Contact Socket 2.0 mm

crimp/ 0.35 - 2.50 mm²
Item: 60.003.11



Copyright by Electro-Matic Integrated, INC.
All rights, including rights created by patent grant or registration
of a utility model or design, are reserved.
Noncompliance will result in seeking damages.

This document is for information only and before utilization
the user must reconfirm actuality.
Subject to technical changes.

Electro-Matic Integrated, INC.
23410 Industrial Park Court
48335 Farmington Hills, MI
USA

E-Mail: ConnectivityEng@electro-matic.com
Web: www.emintegrated.com

issue: 05.04.2020

Main Dimensions
Plug angled 90° adjustable

*for max. wire cross-section
pay attention to the
cross-section of used contacts