

923 Plug angled 90° adjustable

8-pin
 EMC - Shielding
 Earth-to-Housing Connection according to VDE 0627

Technical Data

number of pins	8
power	4 (3+PE)
signal	4
temperature range	-20 °C to 130 °C
clamping range	Ø 9,5 mm to Ø 14,5 mm
protection type	when connected IP 66/67

Electrical Data

	power	signal
rated current	max. 30 A*	max. 7 A*
rated voltage	630V (AC/DC)	250 V (AC/DC)
rated insulation voltage (L-L)	6000 V	2500 V

mating cycles	500
---------------	-----

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PA 6.6 mod., UL 94/V0
seals	FKM
clamp ring	brass / nickel plated


Contacts (not part of product contents)

Tools (not part of product contents)

B SD A 108 NN 00 58 0200 A00



Contact Arrangement
 mating view



Copyright by Electro-Matic Integrated, INC.
 All rights, including rights created by patent grant or registration of a utility model or design, are reserved.
 Noncompliance will result in seeking damages.

This document is for information only and before utilization the user must reconfirm actuality.
 Subject to technical changes.

Electro-Matic Integrated, INC.
 23410 Industrial Park Court
 48335 Farmington Hills, MI
 USA

E-Mail: ConnectivityEng@electro-matic.com
 Web: www.emintegrated.com

issue: 05.04.2020

Main Dimensions
 Plug angled 90° adjustable

*for max. wire cross-section
 pay attention to the
 cross-section of used contacts