

Technical Data

number of pins	9
power	4 (3+PE)
signal	5
temperature range	-20 °C to 130 °C
clamping range	Ø 11.0 to Ø 14.0
protection type	when connected IP 66/67

Electrical Data

rated current	power max. 30 A*	signal max. 7 A*
rated voltage	630V (AC/DC)	250 V (AC/DC)
rated insulation voltage (L-L)	6000 V	2500 V

mating cycles	500
---------------	-----

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PA 6.6 mod., UL 94/V0
seals	FKM
clamp ring	plastic

Contacts (not part of product contents)

Tools (not part of product contents)


cable press-in locktec
Item: WA10365

Assembly Tool locktec
Item: WM10527

B KU A 145 NN 00 24 L135 A00



Contact Arrangement
mating view



Copyright by Electro-Matic Integrated, INC.
All rights, including rights created by patent grant or registration
of a utility model or design, are reserved.
Noncompliance will result in seeking damages.

This document is for information only and before utilization
the user must reconfirm actuality.
Subject to technical changes.

Electro-Matic Integrated, INC.
23410 Industrial Park Court
48335 Farmington Hills, MI
USA
E-Mail: ConnectivityEng@electro-matic.com
Web: www.emintegrated.com

issue: 03.04.2020

Main Dimensions
Extension

*for max. wire cross-section
pay attention to the
cross-section of used contacts