

Technical Data

number of pins	9
power	4 (3+PE)
signal	5
temperature range	-20 °C to 130 °C
clamping range	Ø 7.5 mm to Ø 12.0 mm
protection type	when connected IP 66/67

Electrical Data

rated current	power max. 30 A*	signal max. 7 A*
rated voltage	630V (AC/DC)	250 V (AC/DC)
rated insulation voltage (L-L)	6000 V	2500 V

mating cycles	500
---------------	-----

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PA 6.6 mod., UL 94/V0
seals	FKM
contacts	brass / gold plated
contacts	brass / gold plated
clamp ring	brass / nickel plated

Contacts

Item:	60.254.11
type	Contact Socket 2.0 mm
cross section	crimp/ 0.35 - 2.50 mm ²
contact resistance	< 3 mOhm

Item:	60.001.11
type	Contact Socket 1.0 mm
cross section	crimp/ 0.14 - 1.00 mm ²
contact resistance	< 5 mOhm

Tools (not part of product contents)

digital crimping tool for 1mm-/2 mm- contacts
 Item: C0.236.00

analog crimping tool for 1 mm-/2 mm- contacts
 Item: C0.201.00

positioning insert for ø2mm contacts
 Item: C0.004.00

B ST A 200 FR 44 48 0235 A00




Contact Arrangement
 mating view



Contact Socket 2.0 mm
 crimp/ 0.35 - 2.50 mm²
 Item: 60.254.11



Contact Socket 1.0 mm
 crimp/ 0.14 - 1.00 mm²
 Item: 60.001.11



Copyright by Electro-Matic Integrated, INC.
 All rights, including rights created by patent grant or registration
 of a utility model or design, are reserved.
 Noncompliance will result in seeking damages.

This document is for information only and before utilization
 the user must reconfirm actuality.
 Subject to technical changes.

Electro-Matic Integrated, INC.
 23410 Industrial Park Court
 48335 Farmington Hills, MI
 USA
 E-Mail: ConnectivityEng@electro-matic.com
 Web: www.emintegrated.com

issue: 26.03.2020

Main Dimensions

Plug

*for max. wire cross-section
 pay attention to the
 cross-section of used contacts