

speedtec - ready

6-pin

EMV - shielding

Earth-to-Housing Connection according to VDE 0627

Anti-vibration o-ring

Technical Data

number of pins	6
power	4 (3+PE)
signal	2
temperature range	-20 °C to 130 °C
clamping range	Ø 9.0 mm to Ø 16.0 mm
protection type	when connected IP 66/67

Electrical Data

	power	signal
rated current	max. 75 A*	max. 30 A*
rated voltage	630V (AC/DC)	250 V (AC/DC)
rated insulation voltage (L-L)	6000 V	4000 V

mating cycles	500
---------------	-----

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree	3
over voltage category	III
max. height for operation	2000 m

Material

housing	zinc diecast / nickel plated
insulation insert	PA 6.6 mod., UL 94/V0
seals	FKM
contacts	brass / gold plated
contacts	brass / gold plated
clamp ring	zinc diecast / nickel plated

Contacts

Item:	61.039.11
type	Contact Pin ø3.6 mm
cross section	crimp/ 1,50 - 10,00 mm ²
contact resistance	< 1 mOhm

Item:	61.107.11
type	Contact Pin ø2.0 mm
cross section	crimp/ 0,35 - 2,50 mm ²
contact resistance	< 3 mOhm

Tools (not part of product contents)

analog crimping tool for 3,6 mm contacts
 Item: C0.008.00

digital crimping tool for 1mm-/2 mm- contacts
 Item: C0.236.00

analog crimping tool for 1 mm-/2 mm- contacts
 Item: C0.201.00

C KU A 267 MR 48 44 0051 A00




Contact Arrangement
 mating view



Contact Pin ø3.6 mm
 crimp/ 1.50 - 10.00 mm²
 Item: 61.039.11



Contact Pin ø2.0 mm
 crimp/ 0.35 - 2.50 mm²
 Item: 61.107.11



Copyright by Electro-Matic Integrated, INC.
 All rights, including rights created by patent grant or registration
 of a utility model or design, are reserved.
 Noncompliance will result in seeking damages.

This document is for information only and before utilization
 the user must reconfirm actuality.
 Subject to technical changes,

Electro-Matic Integrated, INC.
 23410 Industrial Park Court
 48335 Farmington Hills, MI
 USA
 E-Mail: ConnectivityEng@electro-matic.com
 Web: www.emintegrated.com

issue: 04.08.2020

Main Dimensions
 Extension

*for max. wire cross-section
 pay attention to the
 cross-section of used contacts